


## Vanguard Guardian+ NVR-L Series

4 Channel, 4 PoE, 4K H.265 NVR



All in One for ATM Installation: Built in PoE Switch / Redundant Storage /Bandwidth management and Quality of Service/ Secure ATM Integration/ Alarm Inputs Integration

- Up to 4 channel with 1080P real-time live view
- H.265/H.264 decoding
- Max 200Mbps incoming bandwidth
- Up to 8Mp resolution preview playback
- HDMI/VGA simultaneous video output
- 4 channel synchronous real-time playback, GRID interface and etc.
- ONVIF Version 2.4 conformance
- Built in 4 PoE Ports
- Support IPC UPnP
- Support Secure ATM Text Integration
- Support 2 SATA HDDs up to 24TB, 2 USB (1 USB3.0)
- SMART Redundancy Function
- Automatic Network Recovery
- Multiple network monitoring: Web viewer, CMS





## Vanguard Guardian+ NVR-L4+ Series (ATM Version)

| System               |  |
|----------------------|--|
| Main Processor       | High Performance Dual Core Embedded  |
| Operating System     | Embedded LINUX   |
| Motherboard          | Embedded Board (Support 7x24 operation)  |
| Interface            | Local GUI &WEB GUI   |
| Video                |  |
| IP Camera Input      | 4 CH   |
| Video Out            | 1 HDMI, 1 VGA  |
| Recording            |  |
| Compression          | H.265+/H.265/H.264   |
| Alarm Recording      | Video loss, Camera blank, Motion detection,<br>External alarm  |
| Recording Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/720P/D1.   |
| Recording Rate       | 200Mbps  |
| Recording Mode       | Manual, Schedule (Regular (Continuous), MD<br>(Video detection: Motion detection, Camera<br>blank, Video loss, Alarm, Stop       |
| Backup Mode          | Network download / USB HDD / USB<br>CD&DVD-RW / eSATA Device   |
| Display              |  |
| Display Split        | 1/4  |
| Tour Display         | Support  |
| OSD                  | Camera title, Date, Time, Transaction Details  |
| Privacy Masking      | 4 customized zones for privacy masking for each area   |
| Storage              |  |
| Internal HDD         | 2 SATA ports each up to 12TB with Storage<br>Redundancy and SMART Redundancy<br>Function   |
| Network              |  |
| Interface            | 1 xRJ45 10/100/1000Mbps + 1 Independent<br>1000Mbps + 4 Ports for IPC  |
| Network Function     | HTTP, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, ANR, Alarm Server, IP Search                   |
| Remote Operation     | Monitor, PTZ control, Playback, System setting, File download, Log information, Search Video by Card Number, Transaction Number. |

| MD & Alarm          |  |
|---------------------|--|
| Trigger Events      | Recording, PTZ movement, Tour, Alarm, Email, FTP, Buzzer & Screen tips               |
| Motion Detection    | Zones: 396(22×18), Sensitivity: 1~6 (level 6 is highest) Video Loss and Camera Blank |
| Video Loss, Blank   | Support  |
| Auxiliary Interface |  |
| USB                 | 2 USB ports (1 on the front-panel, 1 on the rear panel)                              |
| General             |  |
| Power Supply        | DC 12/4A (Input 220VAC)  |
| Working Environment | -10 ~+55°C / 10~90%RH / 86~106kpa  |
| Dimension (W×D×H)   | Mini 1U, 375 mm × 285 mm × 50 mm   |
| Weight              | 2kg (without HDD)  |
| Warranty            | Vanguard 1-year warranty and<br>Vanguard Extended Warranty option                    |